

# Barristo Enterprises, Inc., dba SureHold®

## SAFETY DATA SHEET

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product Identifier 90 Second Epoxy, Part A - Hardener (SH) 335

#### Relevant identified uses of the substance or mixture and uses advised against

Intended Use: Epoxy curing agent

#### Details of the supplier of the safety data sheet

Barristo Enterprises, Inc. dba SureHold  
3717 N Ravenswood Avenue, Suite 243  
Chicago, IL 60613  
Email: [info@surehold.com](mailto:info@surehold.com)  
Website: [www.surehold.com](http://www.surehold.com)  
Phone: 773-472-8592; Toll Free 800-881-4495  
Fax: 773-535-1750

#### 24 Hour Emergency telephone number

Emergency Tel: 800-881-4495

#### Email address


[information@surehold.com](mailto:information@surehold.com)

### 2. HAZARDS IDENTIFICATION

#### Classification of the substance or mixture

Health	Skin Corrosion/Irritation	Category 1B
	Skin Sensitization	Category 1
	Serious Eye Damage	Category 1
	Aquatic Hazard (Acute)	Category 3

#### Label elements:

Hazard pictogram:	
	
Single word:	DANGER
Emergency Overview:	Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

#### Precautionary Statement - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wash skin and hands thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Contaminated work clothing should not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Wash contaminated clothing before reuse.

#### Precautionary Statement - Response

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.  
IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If exposed or concerned: Get medical advice/attention.  
If skin or rash occurs: Get medical advice/attention.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Store in a well-ventilated place. Keep container tightly closed.

**Precautionary Statement – Storage****Precautionary Statement – Disposal**

Dispose of in a manner consistent with federal, state and local regulations.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No	Weight - %
Mercaptan/amine polymer system	Proprietary	75-85%
3,6-DIAZAOCTANETHYLENEDIAMINE	112-24-3	5-10%
Bis (2-dimethylaminoethyl) Ether	3033-62-3	1-5%

**4. FIRST AID MEASURES****Description of first aid measures**

Inhalation: IF INHALED: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Skin contact: IF ON SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms reoccur. Wash clothing before reuse.

Eye contact: IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Ingestion: If swallowed: DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Signs and Symptoms of Overexposure: EYES: Causes eye irritation.  
SKIN: Causes skin irritation.  
INGESTION: Ingestion of this material can cause mouth, throat, esophageal and gastrointestinal tract irritation.  
INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.  
ACUTE EFFECTS: Slightly irritating to eyes and respiratory tracts.  
CHRONIC EFFECTS: Avoid contact with eyes; may cause redness, irritation and conjunctivitis.

**5. FIRE FIGHTING MEASURES**

**Flammable Class:** Not flammable.

**Extinguishing media:** Use alcohol foam, carbon dioxide or water spray when fighting fires involving this material.

**Hazardous Combustion Products:** Combustion products may include: oxides of carbon, nitrogen and sulfur; hydrogen sulfides.

**Advice for firefighters:** Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.  
As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

**Hazardous Decomposition Products:** Combustible by-products of carbon monoxide/dioxide, hydrogen sulfide and oxides of sulfur.

**6. ACCIDENTAL RELEASE MEASURES**

**Small Spill:** Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material

**Large Spill:** and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.  
Stop leak if without risk. Move containers from spill area. Absorb release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material, e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.

**Environmental Precautions**

**Water Spill:** This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.  
**Land Spill:** This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.  
**Air Spill:** This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

**General Procedures:** Implement cleanup procedures.

If in public area, keep public away and advise authorities.  
Recover by pumping (use an explosion proof or hand pump) or with a suitable absorbent.

**Special Protective Equipment**

Use plastic/rubber gloves, chemical splash goggles or safety glasses with side shields.

**Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

**7. HANDLING AND STORAGE**

**General Procedures:** Use with adequate ventilation. Avoid contact with eyes, skin and clothing.  
**Handling:** Avoid breathing (dust, vapor, mist, gas). Avoid contact with skin, eyes and clothing. Keep container closed when not in use.  
**Storage:** Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition. Suggested storage conditions: ambient room temperature (70°F/21°C).  
**Comments:** Loading Temperature: Not established.  
Loading/Unloading Viscosity: Not established.  
Storage Pressure: Not established.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Control parameters**

Chemical Name	ACGIH TLV	OSHA PEL	Other
Bis (2-dimethylaminoethyl) Ether	0.05 ppm (TWA) 0.15 ppm (STEL)	Not data available	None

**Exposure controls**

Engineering controls: Use only in a well ventilated area.  
Eye/Face protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.  
Skin protection: Wear rubber gloves to avoid prolonged skin contact.  
Respiratory: Use only in a well-ventilated area.  
Protective clothing: Wear protective clothing. Launder contaminated clothing before reuse.  
Other Use Precautions: Avoid contact with eyes and skin. Wash thoroughly after handling.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

Physical state: Liquid

Appearance:	Pale yellow viscous liquid
Odor:	Sulfur odor
Odor threshold	No data available
pH:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point:	>93°C (200°F) Method: Pensky-Martens CC
Evaporation rate :	No data available
Flammability:	
Upper flammability limit:	No data available
Lower flammability limit:	No data available
Vapor Pressure:	No data available
Vapor Density (Air=1):	No data available
Solubility:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity	14000 to 18000 Centipoise

**Other information**

Specific gravity:	1.12
VOC content:	0 g/L

**10. STABILITY AND REACTIVITY****Hazardous Polymerization**

Under normal conditions of storage and use, hazardous reactions will not occur.

**Chemical stability**

Stable.

**Conditions to avoid**

Avoid storage near large masses of epoxy resins.

**Incompatible materials**

Avoid strong oxidizing agents and amines especially when hot.

**Hazardous decomposition products**

Combustible by-products of carbon monoxide/dioxide, hydrogen sulfide and oxides of sulfur.

**11. TOXICOLOGICAL INFORMATION****Acute toxicity:**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	Health Effect/Target Organs
3,6-DIAZAOCTANETHYLENEDIAMINE	2500 mg/kg (Rat)	550 mg/L (Rabbit)	----	
Bis (2-dimethylaminoethyl) Ether	2500 mg/kg (Rat)	805 mg/L (Rabbit)	----	

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin Effects:** Irritating to skin. May cause allergic skin reaction with prolonged contact.

**Carcinogenicity:** No known significant effect or critical hazards.

**Sensitization:** Irritating to skin. May cause allergic skin reaction with prolonged contact.

**Mutagenicity:** No known significant effect or critical hazards.

**12. ECOLOGICAL INFORMATION**

**Environmental Data:** Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

**Ecotoxicological Information:** Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

**Bioaccumulation/Accumulation:** Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

**13. DISPOSAL CONSIDERATIONS**

**Disposal of wastes** The generation of waste should be avoided or minimized whenever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or lines may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**14. TRANSPORT INFORMATION****DOT**

**UN/ID No.:** UN3267  
**Proper shipping name:** Corrosive Liquid, Basic, Organic, N.O.S. (3,6 Diazaoctanethylenediamn)  
**Hazardous Class:** 8  
**Packaging Group:** III  
(LTD QTY, IP VOL LESS THAN OR EQUAL TO 5.0L)

**IATA**

**UN/ID No.:** UN3267  
**Proper shipping name:** Corrosive Liquid, Basic, Organic, N.O.S. (3,6 Diazaoctanethylenediamn)  
**Hazardous Class:** 8  
**Packaging Group:** III  
(LTD QTY, IP VOL LESS THAN OR EQUAL TO 5.0L)

**IMGD**

**UN/ID No.:** UN3267  
**Proper shipping name:** Corrosive Liquid, Basic, Organic, N.O.S. (3,6 Diazaoctanethylenediamn)  
**Hazardous Class:** 8  
**Packaging Group:** III  
(LTD QTY, IP VOL LESS THAN OR EQUAL TO 1.0L)

**COMMENTS**

\* This product may be shipped as EXCEPTED QUANTITIES OF CLASS 8, UN3267 (IP VOL LESS THAN OR EQUAL TO 0.03 L, OP VOL LESS THAN OR EQUAL TO 1.0 L)

**15. REGULATORY INFORMATION****United States****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

Fire No  
Pressure Generating No

**SUREHOLD® 90 Second Epoxy Part A (Hardener) & Part B (Resin)**Revision 3  
Revision Date 10-June-2016

Reactivity	No
Acute	Yes
Chronic	No

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

Chemical Name	CAS
Mercaptan/amine polymer system	
3,6-DIAZAOCTANETHYLENEDIAMINE	112-24-3
Bis (2-dimethylaminoethyl) Ether	3033-62-3

TSCA Status: All ingredients in this mixture are in compliance with TSCA.

**16. OTHER INFORMATION**

NFPA	Health hazards 2	Flammability 1	Instability 0	---
HMIS	Health hazards 2	Flammability 1	Physical hazards 0	Personal protection

NFPA (National Fire Protection Association)  
HMIS (Hazardous Material Information System)

Further information This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties. Substances have been classified in accordance with Regulation (EC) 1272/2008 (CLP).

**Barristo Enterprises, Inc., dba SureHold®****SAFETY DATA SHEET****1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY**

Product Identifier 90 Second Epoxy, Part B - Resin (SH) 335

**Relevant identified uses of the substance or mixture and uses advised against**

Intended Use: Resin

**Details of the supplier of the safety data sheet**Barristo Enterprises, Inc. dba SureHold  
3717 N Ravenswood Avenue, Suite 243  
Chicago, IL 60613  
Email: [info@surehold.com](mailto:info@surehold.com)  
Website: [www.surehold.com](http://www.surehold.com)  
Phone: 773-472-8592; Toll Free 800-881-4495  
Fax: 773-535-1750**24 Hour Emergency telephone number**

Emergency Tel: 800-881-4495

**Email address**[information@surehold.com](mailto:information@surehold.com)**2. HAZARDS IDENTIFICATION****Classification of the substance or mixture**

Health	Skin Irritation	Category 2
	Eye Irritation	Category 2B
	Skin Sensitization	Category 1B
	Reproductive Toxicity	Category 2

**Label elements:**

Note: this product is a consumer product and is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for labeling of consumer products takes precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.

**Hazard pictogram:****Single word:**

WARNING

**Emergency Overview:**

Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Suspect of damaging fertility or the unborn child.

**Precautionary Statement -  
Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wash skin and hands thoroughly after handling.  
Contaminated work clothing should not be allowed out of the workplace.

<b>Precautionary Statement - Response</b>	Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing. Wash contaminated clothing before reuse. Collect spillage. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice attention.
<b>Precautionary Statement – Storage</b>	Store in a well-ventilated place. Keep cool.
<b>Precautionary Statement – Disposal</b>	Dispose of in a manner consistent with federal, state and local regulations.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight - %
Epoxy resin	25068-38-6	90-100%

### 4. FIRST AID MEASURES

#### Description of first aid measures

General advice	If symptoms persist, call a physician.
Inhalation:	IF INHALED: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	IF ON SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms reoccur. Wash clothing before reuse.
Eye contact:	IF IN EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel.
Ingestion:	IF SWALLOWED, Do not induce vomiting. Keep individual calm. Get medical attention and show container label.
Signs and Symptoms of Overexposure:	EYES: Causes eye irritation. SKIN: Irritating to skin. May cause allergic skin reaction with prolonged contact. SKIN ABSORPTION: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water. INGESTION: May be irritating. Seek medical advice. INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation. ACUTE EFFECTS: Slightly irritating to eyes and respiratory tracts. CHRONIC EFFECTS: Frequent prolonged contact may irritate the skin and cause a skin rash (dermatitis).

### 5. FIRE FIGHTING MEASURES

<b>Flammable Class:</b>	Not flammable.
<b>Extinguishing media:</b>	Use alcohol foam, carbon dioxide or water spray when fighting fires involving this material.
<b>Hazardous Combustion Products:</b>	Combustion products may include and are not limited to: Carbon monoxide, carbon dioxide and phenolics.
<b>Advice for firefighters:</b>	Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition. As in any fire, wear self-contained breathing apparatus pressure demand (MSHA/NIOSH approved or equivalent) and full protective gear.
<b>Hazardous Decomposition Products:</b>	Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition.



**6. ACCIDENTAL RELEASE MEASURES**

- General Procedures:** Contain spilled material if possible. Absorb with materials such as: Sand. Polypropylene fiber products, Polyethylene fiber products. Remove residual with soap and hot water. Collect in suitable and properly labeled containers. Residual can be removed with solvent. Solvents are not recommended for clean-up unless the recommended exposure guidelines and safe handling practices for the specific solvent are followed. Consult appropriate solvent Safety Data Sheet for handling information.
- Comments:** This product is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

**Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

**7. HANDLING AND STORAGE**

- General Procedures:** Use with adequate ventilation. Avoid contact with eyes, skin and clothing.
- Handling:** Avoid breathing (dust, vapor, mist, gas). Avoid contact with skin, eyes and clothing. Keep container closed when not in use.
- Storage:** Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition. Storage temperature: ambient room temperature (70°F/21°C)
- Comments:** Loading Temperature: Not determined.  
Loading/Unloading Viscosity: Not determined.  
Storage Pressure: Not determined.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Engineering controls:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are not applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

**Personal Protective Equipment**

- |                       |   |
|-----------------------|---|
| Eye/Face protection   | For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles. |
| Skin protection       | Wear rubber gloves and an apron to avoid prolonged skin contact.  |
| Respiratory           | Use only in a well-ventilated area.   |
| Protective Clothing   | Wear rubber gloves and apron.   |
| Other Use Precautions | Avoid contact with skin and eyes. Wash thoroughly after handling.   |

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

- |  |  |
|--|--|
| Physical state:                          | Viscous Liquid   |
| Appearance:                              | Light yellow colored viscous liquid                    |
| Odor:                                    | Mild odor  |
| Odor threshold                           | No data available                                      |
| pH:                                      | No data available                                      |
| Melting point/freezing point:            | No data available                                      |
| Initial boiling point and boiling range: | No data available                                      |
| Flash point:                             | 264°C to 268°C (507°F to 514°F) Method: Tag Closed Cup |
| Evaporation rate:                        | No data available                                      |
| Density:                                 | 1.16 g/cm <sup>3</sup> at 25°C (77°F)                  |
| Flammable Limits:                        |  |
| Upper flammability limit:                | No data available                                      |
| Lower flammability limit:                | No data available                                      |
| Vapor Pressure:                          | No data available                                      |

Vapor Density:	No data available
Solubility:	5.4 to 8.4 mg/L at 20°C (68°F)
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity	10000 to 20000 mPa. S. at 25°C (77°F)
Molecular Weight:	No data available

**Other information**

Specific gravity:	1.16
VOC content:	0 g/L

**10. STABILITY AND REACTIVITY****Hazardous Polymerization**

Will not occur.

**Chemical stability**

Stable.

**Conditions to avoid**

Avoid temperatures above 300°F (148°C).

**Incompatible materials**

Strong acids, oxidizing agents, mineral and organic bases, and especially aliphatic amines.

**Hazardous decomposition products**

Carbon Monoxide, aldehydes, acids and other organic substances may be formed during combustion (&gt;500°F) temperature degradation.

**11. TOXICOLOGICAL INFORMATION****Acute toxicity:**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Epoxy resin (Bisphenol A)	>2000 mg/kg (Rat)	2000 mg/kg (Rabbit)	----

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Eye Effects:** Prolonged or repeated skin contact may cause irritation.**Skin Effects:** May cause sensitization.**Carcinogenicity:** IARC: Not listed.  
NTP: Not listed.  
OSHA: Not listed.**Reproductive Effects:** In animal studies, did not interfere with reproduction.**Germ Cell Mutagenicity:** In vitro toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.**12. ECOLOGICAL INFORMATION****Environmental Data:** Do not flush to sewer.**Ecotoxicological Information:** Rainbow trout LC50, semi-static test, 96 h: 2 mg/L; Water flea EC50, static test, 48 h, immobilization: 1.8 mg/L; Bacteria IC50, 18 h: >42.6 mg/L.**Bioaccumulation/Accumulation:** Bioconcentration potential is moderate (BCF 100 to 3000 or Log Pow 3 to 5).**Notes:** Material is toxic to aquatic organisms (LC50 between 1 and 10 mg/L in the most sensitive species).**13. DISPOSAL CONSIDERATIONS****Disposal of wastes** Dispose of following all Local Authority requirements for disposal.**14. TRANSPORT INFORMATION****DOT**

**SUREHOLD® 90 Second Epoxy Part A (Hardener) & Part B (Resin)**Revision 3  
Revision Date 10-June-2016

**Un/ID No.:** UN3082  
**Proper shipping name:** Not regulated for transport (IP VOL LESS THAN OR EQUAL TO 450.0 L)  
**Hazardous Class:** 9 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL-A EPOXY RESIN)  
**Packaging Group:** III (IP VOL GREATER THAN 450.0 L)

**IATA**

**Un/ID No.:** UN3082  
**Proper shipping name:** ID 8000, CONSUMER COMMODITY  
**Hazardous Class:** 9 (IP VOL GREATER THAN 450.0 L)  
**Packaging Group:** III (LTD QTY, IP VOL LESS THAN OR EQUAL TO 5.0 L)\*

**IMGD**

**Un/ID No.:** UN3082  
**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (BISPHENOL-A EPOXY RESIN)  
**Hazardous Class:** 9  
**Packaging Group:** III (LTD QTY, IP VOL LESS THAN OR EQUAL TO 5.0 L)\*

**COMMENTS:** \* This product may be shipped as EXCEPTED QUANTITIES OF CLASS 9, UN3082 (IP VOL LESS THAN OR EQUAL TO 0.03 L, OP VOL LESS THAN OR EQUAL TO 1.0 L)

**15. REGULATORY INFORMATION****United States****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

Fire	No
Pressure Generating	No
Reactivity	No
Acute	Yes
Chronic	No

**Title III Notes:**

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

**TSCA 9 (TOXIC SUBSTANCE CONTROL ACT)**

<b>Chemical Name</b>	<b>CAS</b>
Epoxy resin (Bisphenol A)	25068-38-6

TSCA Status All chemical substance in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**California Proposition 65**

Warning: This product contains a chemical(s) known to the state of California to cause cancer and birth defects or other reproductive harm. (Bisphenol A Resin CAS 25085-99-8)

**16. OTHER INFORMATION**

NFPA	Health hazards 1	Flammability 1	Instability 0	---
HMIS	Health hazards 1	Flammability 1	Physical hazards 0	Personal protection

NFPA (National Fire Protection Association)  
 HMIS (Hazardous Material Information System)

Further information This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties. Substances have been classified in accordance with Regulation (EC) 1272/2008 (CLP).